



QM-WRPPDS: Professional matte stay-flat polypropylene

This 10 mil polypropylene has a specially formulated coating on the backside to force the media to lay flat on both sides. WRPPDS has very good tear resistance and its smooth matte, microporous top coating gives it the ability to reproduce accurate color. This is an ideal product for indoor signage.



Benefits:

- Water Resistant
- Superior Color Gamut
- Rapid Drying Times
- Tear Resistance

Applications:

- POP Display
- Indoor Banner
- Posters

Registered Latex Developer

TECHNICAL DATA: QM-WRPPDS – PROFESSIONAL MATTE STAY-FLAT POLYPROPYLENE

SURFACE FINISH:	Aqueous Matte	DURABILITY:	<i>Indoor: Up to 1 year Outdoor: Up to 6 months</i>
BASE MATERIAL:	Polypropylene	ROLL LENGTH:	100 FT. 200 FT.
BASE WEIGHT:	145 GSM +/- 10%	ROLL WIDTHS:	24, 36, 42, 50, 60"
CALIPER:	10 Mil +/-1	CORE:	3" with 2" Adapter (36" X 200' available on 2" core only)
BRIGHTNESS:	106 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Only
WHITENESS:	136 (Ganz Whiteness CIE)	INK RECOMENDATIONS:	AQUEOUS UV LATEX
GLOSS MEASUREMENT:	4 +/- 10% by angle of 60°		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

